DATASHEET · UPHOLSTERY FABRIC

Linen look upholstery fabric

ES2512

Woven upholstery fabric with a linen look in 93% recycled polyester and 7% viscose. For sofas, chairs, cushions and seat pads.

MATERIAL	WEIGHT	WIDTH	ABRASION	ROLL
93% recycled polyester, 7% viscose	300 g/m² ± 5%	145 cm ± 2 cm	50,000 Martindale	45 m

Technical data

PROPERTY	METHOD	RESULT
Abrasion resistance (Martindale)	EN ISO 12947-2	50,000 revs
Pilling after 2,000 revs	EN ISO 12945-2	4-5 (scale 1-5)
Seam slippage, warp / weft	EN ISO 13936-2	2.5 / 3.2 mm
Tensile strength, warp / weft	EN ISO 13934-1	870 / 866 N
Tear strength, warp / weft	EN ISO 13937-3	75.4 / 105.2 N
Colour fastness to rubbing, dry / wet	EN ISO 105-X12	5 / 5 (scale 1-5)
Colour fastness to light	EN ISO 105-B02	4 (scale 1-8)
AZO dyes		not detectable
Chemicals	(EC) 1907/2006	REACH compliant

CHARACTER

A linen look in recycled material: the polyester is made from recycled post-consumer polyester, material that has already been used once.

CARE

Wipe up spills straight away with a damp, white cloth. Always test on a hidden spot first.

ORDERING

Order from 10 m per colour. A full roll is 45 m. All 16 colours share the same weight, width and abrasion resistance, so they can be mixed in one project.

Colours

16 colours

ES2512-001 off-white	ES2512-005 natural 1	ES2512-010 navy blue	ES2512-014 grey
ES2512-002 linen	ES2512-006 ochre	ES2512-011 denim	ES2512-015 ash grey
ES2512-003 dark beige	ES2512-008 forest green	ES2512-012 aqua	ES2512-016 anthracite
ES2512-004 natural 2	ES2512-009 dusky pink	ES2512-013 silver	ES2512-017 dark grey

Test results are indicative averages from several samples, measured by an independent laboratory using the methods above (specified to DIN EN 14465). Slight shade differences between production batches can occur. Pilling and single pulled threads can occur in all upholstery fabrics. Dark fabrics can transfer colour to light ones, and sunlight and heat can change the colour over time.